702/703/704 Model Number Breakdown

7	0	2	0	9	G	1	A	C	C	O	O	S

Series
702
703- Heat Pump
704 ï Extrended range heat pump

Cool BTUâs
09 ï 9000
12 ï 12000
15 ï 15000

Voltage
A ï 115
G ï 208/230
E - 265

Fan Control
O ï Standard Continuous Fan
C ï Cycling air, Elec Heat
H ï Cycling Air, Hydronic Heat

Paint
O - Standard

Return Air Options

O	Std, Btm inlet
F	Front Inlet

Heat Option

Heat Option	KW 208/230 - 265
0	None
1	2.0/2.4 ï N/A
2	3.0/3.3 ï N/A
3	N/A ï 3.25
4	3.7/4.5 ï N/A
5	4.0/N/A ï 3.98
H	Hot Water
S	Steam

Control

Control	Description
A	MCO ï UL Standard
B	ACO UL
C	MCO, Prog Rly, 24V, UL
D	ACO, Prog Rly, 24V, UL
E	MCO. Sec Grd, UL, 24V
F	ACO. Sec Grd, UL, 24V
G	Mstr/Slave or Remote UL, 24V
H	MCO 115V Emerg Pwr
J	ACO 115V Emerg Pwr
K	MCO, Prog Rly, 120V, UL
L	ACO, Prog Rly, 120V, UL
M	MCO. Sec Grd, UL, 120V
N	ACO. Sec Grd, UL, 120V
P	Mstr/Slave or Rem, UL, Prog Rly 24V

Damper

Damper	Description
A	No Damper
B	Motorized, no filter
C	Manual, no filter
D	Motorized, w/filter
E	Manual w/filter
F	Motorized Hi Vol
G	Manual Hi Volume

Cord Options

S	Std LH 30ò cord
N	Pigtail
P	LH 78ò cord